

Thermal imager

testo 885 – professional, versatile and precise thermography

Infrared resolution 320 x 240 pixels

SuperResolution technology with 640 x 480 pixels

Thermal sensitivity < 30 mK

Flexibility thanks to its rotating handle and rotating, fold-out display

Exchangeable lenses

Measurement mode for detecting mould-risk areas

High temperature measurement up to 1200 °C

Panorama image assistant

SiteRecognition technology



The thermal imager testo 885 is the professional measuring instrument for the high-precision detection of anomalies and damage to building shells or interiors. The high-quality infrared measurement system means that energy losses or thermal bridges in building shells can be reliably detected, enabling comprehensive energy consultations to be carried out. Indoor leaks can be reliably located, without needing to

dismantle cable or pipeline systems. The intuitive testo 885 with its rotating handle, fold-out display and lots of helpful functions, such as panorama image assistant and auto-focus, makes it possible to carry out both quick on-site checks as well as comprehensive energy consultations with professional reports simply, reliably and professionally.

Ordering data

testo 885 sets with your selection of lenses

Complete sets in a robust case, each including pro software, SD card, USB cable, carrying strap, lens-cleaning cloth, mains unit, Li ion rech. battery, headset, lens case, lens protection glass, additional rech. battery and fast charging station



Part no.

| | | |
|---|--------------|--|
| testo 885 set with standard and telephoto lens – see above for further set components | 0563 0885 V3 | |
| testo 885 set with standard or telephoto, and super-telephoto lens – see above for further set components | 0563 0885 V5 | |
| testo 885 set with standard, telephoto and super-telephoto lens – see above for further set components | 0563 0885 V6 | |

testo 885 thermal imagers

Part no.

| | | |
|--|--------------|--|
| Thermal imager testo 885 with standard lens in a robust case, including pro software, SD card, USB cable, carrying strap, lens-cleaning cloth, mains unit, Li ion rech. battery and headset | 0563 0885 V2 | |
| Thermal imager testo 885 with super-telephoto lens in a robust case, including pro software, SD card, USB cable, carrying strap, lens-cleaning cloth, mains unit, Li ion rech. battery and headset | 0563 0885 V4 | |

Accessories

| | Code¹⁾ (Initial equipment) | Part no. (Retrofit) |
|--|---|-------------------------------|
| SuperResolution. Four times more measurement values for even more detailed analysis of the thermal images | S1 | 0554 7806 |
| Lens protection glass. Special Germanium protection glass for optimum protection of the lens from dust and scratching | F1 | 0554 0289 |
| Additional battery. Additional lithium-ion rechargeable battery for extending the operating time. | G1 | 0554 8852 |
| Fast battery charger. Desktop charging station for two rechargeable batteries for the optimization of the charging time. | H1 | 0554 8851 |
| High temperature measurement up to +1,200 °C | I1 | ²⁾ |
| Humidity measurement ³⁾ | E1 | ²⁾ |
| Interchangeable telephoto lens 11° x 9° | D1 | ²⁾ |
| Super-telephoto lens 5° x 3.7° | T2 | ²⁾ |
| Process analysis package: image sequence capturing in instrument and fully radiometric video measurement | V1 | 0554 8902 |
| Emission adhesive tape. Adhesive tape, e.g. for reflective surfaces (roll, L.: 10 m, W.: 25 mm), $\epsilon = 0.95$, temperature resistant to +250 °C | | 0554 0051 |
| ISO calibration certificates; Calibration points at 0 °C, +25 °C, +50 °C | | 0520 0489 ⁴⁾ |
| ISO calibration certificates; Calibration points at 0 °C, +100 °C, +200 °C | | 0520 0490 ⁴⁾ |
| ISO calibration certificates; Freely selectable calibration points in the range -18 to +250 °C | | 0520 0495 ⁴⁾ |

¹⁾ When ordering as first equipment, you receive the accessories directly in the case.

²⁾ Please contact our customer service.

³⁾ Wireless humidity probes only in the EU, Norway, Switzerland, USA, Canada, Colombia, Turkey, Brazil, Chile, Mexico, New Zealand, Indonesia.

⁴⁾ Per lens

⁵⁾ Plus installation

Technical data

| testo 885 | |
|--|---|
| Infrared image output | |
| Infrared resolution | 320 x 240 pixels |
| Thermal sensitivity (NETD) | < 30 mK at +30 °C |
| Field of view/min. focus distance (Lens version) | 30° x 23° / 0.1 m (Standard) 11° x 9° / 0.5 m (Telephoto) 5° x 3.7° / 2 m (Super-telephoto) |
| Geometric resolution (IFOV) (Lens version) | 1.7 mrad (Standard) 0.6 mrad (Telephoto) 0.27 mrad (Super-telephoto) |
| SuperResolution (pixel / IFOV) (Lens version) | 640 x 480 pixels / 1.06 mrad (Standard) 640 x 480 pixels / 0.38 mrad (Telephoto) 640 x 480 pixels / 0.17 mrad (Super-telephoto) |
| Image refresh rate | 33 Hz* |
| Focus | auto / manual |
| Spectral range | 7.5 to 14 µm |
| Image output visual | |
| Image size / min. focus distance | 3.1 MP / 0.5 m |
| Image presentation | |
| Image display | 4.3" LCD touchscreen with 480 x 272 pixels |
| Digital zoom | 1- to 3-fold |
| Display options | IR / real image |
| Video output | USB 2.0 |
| Colour palettes | 9 (iron, rainbow, rainbow HC, cold-hot, blue-red, grey, inverted grey, sepia, Testo) |
| Measurement | |
| Measuring range | -30 to +100 °C / 0 to +350 °C (switchable) 0 to +650 °C (switchable) |
| Accuracy | ±2 °C, ±2 % of m.v. (±3 °C of m.v. at -30 to -22 °C) |
| High temperature measurement - optional | +350 to +1200 °C (not in connection with the telephoto lens) |
| Accuracy | ±2 °C, ±2 % of m.v. |
| Emissivity / reflected temperature | 0.01 to 1 / manual |
| Transmission correction (atmosphere) | ✓ |
| Measuring functions | |
| Display of surface moisture distribution (using manual input) | ✓ |
| Humidity measurement with radio humidity probe (automatic measurement value transfer in real time)** | (✓) |
| Solar mode | ✓ |
| Analysis function | up to 10 measurement points, Hot/Cold Spot Recognition, up to 5 x area measurement (min/max & average), Isotherm and alarm values |

* inside the EU, outside 9 Hz

** Wireless humidity probes only in the EU, Norway, Switzerland, USA, Canada, Colombia, Turkey, Brazil, Chile, Mexico, New Zealand, Indonesia

*** excepting USA, China and Japan

**** Bluetooth only in the EU, Norway, Switzerland, USA, Canada, Colombia, Turkey, Japan, Russia, Ukraine, India, Australia

| testo 885 | |
|--|---|
| Imager equipment | |
| Digital camera with Power LEDs | ✓ |
| Lens version | 30° x 23° (Standard) 11° x 9° (Telephoto) 5° x 3.7° (Super-telephoto) |
| SiteRecognition (measurement site recognition with image management) | ✓ |
| Panorama image assistant | ✓ |
| Laser (laser classification 635 nm, Class 2)*** | Laser marker |
| Voice recording | Bluetooth****/ wired headset |
| Video measurement (via USB) | up to 3 measurement points |
| Process analysis package: image sequence capturing in instrument and fully radiometric video measurement | (✓) |
| Interface | LabVIEW, interface description download on the Testo homepage |
| Image storage | |
| File format single image | .bmt; export option in .bmp, .jpg, .png, .csv, .xls |
| File format video (via USB) | .wmv, .mpeg-1 |
| Storage device | SD card 2GB (approx. 1500 - 2000 images) |
| Power supply | |
| Battery type | Fast-charging, Li-ion battery can be changed on-site |
| Operating time | 4.5 hours |
| Charging options | in instrument / in charger (optional) |
| Mains operation | yes |
| Ambient conditions | |
| Operating temperature range | -15 °C to +50 °C |
| Storage temperature range | -30 to +60 °C |
| Air humidity | 20 to 80 % RH non-condensing |
| Housing protection class (IEC 60529) | IP54 |
| Vibration (IEC 60068-2-6) | 2G |
| Physical specifications | |
| Weight | 1.570 g |
| Dimensions (L x W x H) in mm | 253 x 132 x 111 |
| Tripod mounting | 1/4" - 20UNC |
| Housing | ABS |
| PC software | |
| System requirements | Windows 10, Windows Vista, Windows 7 (Service Pack 1), Windows 8, interface USB 2.0 |
| Standards, tests | |
| EU Directive | 2004 / 108 / EC |

✓ included in delivery

(✓) optional

Overview of variants

| Features | testo 885 | testo 885 Set |
|--|------------------|---------------|
| Infrared resolution | 320 x 240 pixels | |
| Thermal sensitivity (NETD) | < 30 mK | |
| Measuring range | -30 to +650 °C | |
| Image refresh rate | 33 Hz* | |
| SuperResolution | (✓) | (✓) |
| Exchangeable telephoto lens 11° x 9° ***** | (✓) | ✓ |
| Super-telephoto lens 5° x 3.7° ***** | (✓) | ✓ |
| Auto focus | ✓ | ✓ |
| High temperature measurement up to 1,200 °C | (✓) | (✓) |
| Panorama image assistant | ✓ | ✓ |
| SiteRecognition (measurement site recognition with image management) | ✓ | ✓ |
| Laser marker** | ✓ | ✓ |
| Display of surface moisture distribution (by manual input) | ✓ | ✓ |
| Humidity measurement with wireless humidity probe*** (automatic measurement value transfer in real time) | (✓) | (✓) |
| Process analysis package: image sequence capturing in instrument and fully radiometric video measurement | (✓) | (✓) |
| Voice recording using the headset**** | ✓ | ✓ |
| Solar mode | ✓ | ✓ |
| Lens protection glass | (✓) | ✓ |
| Additional battery | (✓) | ✓ |
| Fast battery charger | (✓) | ✓ |

✓ included in delivery
(✓) optional

* inside the EU, outside 9 Hz
 ** excepting USA, China and Japan
 *** Wireless humidity probes only in the EU, Norway, Switzerland, USA, Canada, Colombia, Turkey, Brazil, Chile, Mexico, New Zealand, Indonesia
 **** Bluetooth only in the EU, Norway, Switzerland, USA, Canada, Colombia, Turkey, Japan, Russia, Ukraine, India, Australia
 ***** depending on the selected set